COUNTRY CLIPPER ZERO TURN MOWER

2019 XLT Specifications

Feature	Model				
Product Name	2448KAJ-C300	2454KAJ-C300	2454KAT-C300	2460KAJ-C300	2460KAT-C300
Engine	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V
Horsepower	24	24	24	24	24
Cylinders	2	2	2	2	2
Oil Capacity	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)
Drive System	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon	5 Gallon	5 Gallon
Steering Control	Joystick	Joystick	Twin Lever	Joystick	Twin Lever
Stand-up Deck	Standard	Standard	Standard	Standard	Standard
Pivoting Front Axle	Standard	Standard	Standard	Standard	Standard
Tires, Rear	22x9.5-10	22x11-10	22x11-10	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6	13x6.5-6	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
Length	79"	79"	79"	79"	79"
Height : top of seat back	48"	48"	48"	48"	48"
Width, Tractor (outside rear tires)	47"	49"	49"	49"	49"
Width, Deck w/ Chute	61"	65"	65"	73"	73"
Width, Deck Chute Up	49"	55"	55"	61"	61"
Cutting Width	48"	54"	54"	60"	60"
Cutting Height	2" - 5" (1/4" Increments)				
Deck Construction	Welded 12 Gauge Steel Deck with 12 Gauge Reinforcement, including high impact anti-scalp rollers, 3/8" x 1-1/2" wear bar on leading & trim edge				
Blade Engagement	Electric Clutch, Warner				
Blade Length	17"	18.375"	18.375"	21"	21"
Spindle Assembly	Cast Aluminum housing; 1" diameter shaft; maintenance free				
Blade Tip Speed, approx.	18,000 fpm	18,000 fpm	18,000 fpm	18,000 fpm	18,000 fpm
Weight	798 lbs	803 lbs	803 lbs	846 lbs	846 lbs
Seat	High Back, Enhanced Comfort Seat with adjustable slides				
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step, Hitch Plate				

Due to continuous product improvement, specifications are subject to change without notice.

COUNTRY CLIPPER ZERO TURN MOWER

2019 XLT Specifications

Feature	Model		
Product Name	2648KOJ-C300	2654KOJ-C300	2660KOJ-C300
Engine	Kohler KT745	Kohler KT745	Kohler KT745
Horsepower	26	26	26
Cylinders	2	2	2
Oil Capacity	2 qt (1.9 L)	2 qt (1.9 L)	2 qt (1.9 L)
Drive System	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon
Steering Control	Joystick	Joystick	Joystick
Stand-up Deck	Standard	Standard	Standard
Pivoting Front Axle	Standard	Standard	Standard
Tires, Rear	22x9.5-10	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
Length	79"	79"	79"
Height : top of seat back	48"	48"	48"
Width, Tractor (outside rear tires)	47"	49"	49"
Width, Deck w/ Chute	61"	65"	73"
Width, Deck Chute Up	49"	55"	61"
Cutting Width	48"	54"	60"
Cutting Height	2" - 5" (1/4" Increments)		
Deck Construction	Welded 12 Gauge Steel Deck with 12 Gauge Reinforcement, including high impact anti-scalp rollers, 3/8" x 1-1/2" wear bar on leading & trim edge		
Blade Engagement	Electric Clutch, Warner		
Blade Length	17"	18.375"	21"
Spindle Assembly	Cast Aluminum housing; 1" diameter shaft; maintenance free		
Blade Tip Speed, approx.	18,000 fpm	18,000 fpm	18,000 fpm
Weight	798 lbs	803 lbs	846 lbs
Seat	High Back, Enhanced Comfort Seat with adjustable slides		
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step, Hitch Plate		

Due to continuous product improvement, specifications are subject to change without notice.